



# CURT- Trail Tarpaulin Bodies

**PREMIUM**

**STANDARD**

**EASY**

## BASIC TECHNICAL DATA

### Intermediate frame

Steel or aluminium stringers with an anodized aluminium edge

### Floor

Impregnated waterproof plywood with an antiskid surface

Thickness of the plywood – 24 mm

Cargo securing handles – 14 pieces

### Side walls

Sliding stakes on HESTAL bogies with integrated slat pockets

Side aluminium slats – 2 rows from the bottom, above 4 rows of side aluminium slats

Curtain-type tarpaulin of the side walls on VERSUS bogies

Ratchet system of the tarpaulin side stretching

System of the tarpaulin vertical stretching with steel clamps

Sliding stakes on bogies with slat pockets

Side aluminium slats – 2 rows from the bottom, above 4 rows of side wooden slats

Curtain-type tarpaulin of the side walls

Ratchet system of the tarpaulin side stretching

System of the tarpaulin vertical stretching with steel clamps

Permanent dismantled stakes with slat pockets

Side aluminium slats – 2 rows from the bottom, above 4 rows of side wooden slats

From the outside – tarpaulin with holes for the fastening rope

### Front wall

Front anodized aluminium posts with pockets for side slats

All made of an anodized aluminium panel, up to the full height.

Additionally, from the outside - protective plywood panel to the height of 1250mm from the bottom

Front anodized aluminium posts with pockets for side slats

Impregnated waterproof plywood, 24mm thick, up to the full height

Tarpaulin from the outside

## Back wall

Anodized aluminium posts with pockets for side slats

2 leaf back door made of full aluminium profiles

External pipe closures

Anodized aluminium posts with pockets for side and back slats

Sideboard covered with tarpaulin with holes for the fastening rope

## Roof

Function of two-sided roof lifting

Slided VERSUS ALTO 150, towards the cab of the vehicle

White roof in the standard version

Roof stringers made of aluminium profiles

Crossbeams made of steel profiles, galvanized

Permanent white roof

Rack with aluminium pipes fixed in rubber and metal pockets

Tarpaulin

## Tarpaulin

Basis weight: 900g/m<sup>2</sup>

Tarpaulin colour; RAL at choice

Code XL of the tarpaulin

Basis weight: 900g/m<sup>2</sup>

Tarpaulin colour; RAL at choice

Tarpaulin colour; RAL at choice

## BASIC FITTINGS



Contour marking



High visibility back plates



Outline marker diodes compliant with the EU Traffic Code



2-ton safety belts for securing the rack



Rubber bumpers <sup>(1)</sup>/<sub>(2)</sub>



Fastening rope system



Locked plastic toolbox, 600x415x460 mm



Aluminium door holders <sup>(1)</sup>/<sub>(2)</sub>



Tilting underride guards (anodized aluminium)



Mudguards with anti-splash mud flaps



Handle in the floor



PN EN Certificate "Safe Cargo" (code XL) <sup>(2)</sup>

<sup>(1)</sup> Fittings installed in the STANDARD version

<sup>(2)</sup> Fittings installed in the PREMIUM version